

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 August 2002 (29.08.2002)

PCT

(10) International Publication Number
WO 02/067190 A2

(51) International Patent Classification⁷: **G06K 19/00**

(74) Agent: **REISTER, Andrea, G.**; Covington & Burling,
1201 Pennsylvania Avenue, N.W., Washington, DC 20004-
2401 (US).

(21) International Application Number: **PCT/US02/01284**

(22) International Filing Date: **18 January 2002 (18.01.2002)**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
60/263,756 25 January 2001 (25.01.2001) US
09/988,151 19 November 2001 (19.11.2001) US

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant: **BANK OF AMERICA CORPORATION**
[US/US]; NC1-002-29-01, 101 South Tryon Street, Charlotte, NC 28255 (US).

(72) Inventors: **PENTZ, Jamily**; 4114 Marquesas Avenue, Tega Cay, SC 29708 (US). **BURNS, Emmet**; 201 N. Tryon Street, Charlotte, NC 28255 (US). **COLLINS, Richard, J.**; 148 Whistler Road, Highland Park, IL 60035 (US). **MONTGOMERY, R., Bruce**; 10207 Wildbracken Court, Charlotte, NC 28210 (US). **KENDLE, A., Allen**; 2400 Valencia Terrace, Charlotte, NC 28210 (US).

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **MINIATURE DATA CARD**

WO 02/067190 A2



(57) Abstract: A data card is reduced in size from the conventional standard size credit card. Accessibility of the card is enhanced because the card may be stored in a separate location from conventionally sized cards, such as on a key-chain or similar device. The card of the present invention has a means for storing information, such as a magnetic stripe or computer chip.

MINIATURE DATA CARD

BACKGROUND OF THE INVENTION

This invention relates generally to data cards, such as credit cards, that contain a magnetic stripe or other means of storing information. More particularly, this invention relates to such cards that are small in size.

Cards of various kinds have become ubiquitous in modern society. People often carry a number of cards in their wallet or carrying case, including credit cards, ATM or bank cards, debit cards, "smart cards," insurance cards, a driver's license, identification cards, telephone calling cards, transit cards, library cards, and card-entry hotel keys. An increasing number of consumer transactions require use of these cards, for example, as the form of payment, or as identification necessary for another form of payment or admission. Quick and accurate access to certain individual cards is useful and desirable for both the consumer and the vendor of goods or services.

Typically, consumers store credit cards and other types of cards in a wallet or carrying case. These wallets and carrying cases are frequently equipped with sleeves or slots for holding one or more cards in an arrangement selected by the user. Because of the proliferation of the types and numbers of cards carried by consumers, cards are often held very tightly within these sleeves or slots, making retrieval of a particular card difficult. Difficulty in removing a single selected card increases the time necessary for the transaction, causes stored cards to be frequently reshuffled and potentially disorganized, and increases the likelihood that cards will be dropped or lost.

While the number of cards typically carried by consumers is increasing, most consumers use certain types of cards much more frequently than others. For example, some consumers may use a credit card for nearly every sales transaction, but only rarely, if ever, use calling cards, library cards, or insurance cards. Because a subset of the total number of cards carried by consumers must be accessed repeatedly, it is particularly desirable to improve the accessibility of these types of cards.

One way to improve accessibility of frequently used cards is by allowing them to be stored in a separate location from the traditional wallet or carrying case. Such cards could be stored on key-chains, lanyards, hooks, or other similar devices that are easily retrieved from a

bag or pocket. Thus, when a consumer needs to use the card during a transaction, the card may be quickly retrieved and given to the merchant. This provides an added level of convenience to the consumer by making the payment process quicker and simpler. Additionally, the merchant is able to move customers through the line more quickly, improving customer satisfaction. An additional benefit of storing frequently used cards on a key-chain or like device is that the possibility that the card will be lost is decreased. This is because a single card is much more easily misplaced than a card attached to a key-chain.

Conventionally sized cards, however, are too large and cumbersome to be conveniently stored on a key-chain or like device. The individual items on a key chain must be small and compact so that the key-chain can accommodate numerous items. Further, key-chains and the like are often placed in the pockets of clothing, which may be small. Finally, larger items, such as conventional credit cards, could be bent or otherwise damaged when stored on a device such as a key-chain. Thus, for a card to be effectively carried on a key-chain, its size must be significantly reduced.

The degree to which conventional cards may be reduced in size, however, is limited by the requirements of standard magnetic stripe card readers, such as point-of-sale ("POS") terminals through which the user "swipes" the card to make a purchase or payment. In order to ensure interoperability between the magnetic stripe readers and cards bearing magnetic stripes, the parameters defining the magnetic stripe are governed by the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC). ISO/IEC 7811 provides standards for the physical characteristics of the magnetic stripe including the location of the stripe on the card, the surface profile of the stripe, and the height of the stripe above the card surface. It would be advantageous for a reduced-size card to comply with ISO/IEC 7811, or otherwise be compatible with existing card readers and POS terminals.

Proper functioning of the magnetic stripe is very important. On conventional cards, such as credit cards, magnetic stripes contain encoded information that electronic readers can read to perform a function or confirm identification. For example, on credit and debit cards, the magnetic stripe is usually encoded with specific account information such as the credit card number, cardholder's name, the card expiration date, and a personal identification code. If the electronic device for reading the encoded information cannot properly read the magnetic stripe, the vendor must enter the information manually, using a keypad, telephone, or other similar

device. Manually entering the encoded information adds both indirect and direct costs to the vendor. For example, the additional time necessary to enter the information manually may increase needs for register operators and decrease the vendor's ability to attend to other customer matters. In addition, vendors are frequently charged increased transaction fees by the card issuer for a manually entered transaction.

Thus, a need exists for providing cards, such as credit cards, that are reduced in size from currently used cards, and yet still are operable with currently used readers. Such a card would greatly enhance the efficiency of frequent transactions, including sales transactions, by allowing regularly used cards to be readily and easily retrieved. Further, because such a card could be readily stored on a key-chain or like device, the probability that the card would be lost or misplaced is reduced. Finally, because such a card would be compatible with currently used readers, no redesign of existing card reader technology would be required.

BRIEF SUMMARY OF THE INVENTION

In one aspect, the present invention provides a data card that is reduced in size from conventional credit-card-sized cards, and contains an information storage medium, such as a magnetic stripe or a computer chip, that can be read by existing card reader technology.

In another aspect, a reduced-size data card is provided with a magnetic stripe, which is located near an edge of the card, on which data is encoded. Such a magnetic stripe is reduced in size from the magnetic stripes found on conventionally sized cards, and contains data encoded at a higher bit density than on conventionally sized cards. The magnetic stripe is compatible with existing card reader technology.

In yet another aspect, a reduced-size data card is provided with a hole to allow key-chain storage, and the core may be composed, at least in part, of polyester. Additionally, the surface of a data card of the present invention may also be provided with raised dimples or craters to enhance gripability of the card. Further, information may be printed on the surface of the card, in order to reduce or eliminate the need to emboss the card with raised lettering or embossing.

In still another aspect, a reduced-size data card of the present invention may have an angled edge.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is an illustration of the front view of a conventional credit card.

FIG. 1B is an illustration of the back view of a conventional credit card.

FIG. 2A is an illustration of the front view of one preferred embodiment of the reduced-size data card of the present invention.

FIG. 2B is an illustration of the back view of the embodiment shown in FIG. 2A.

FIG. 3A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 3B is an illustration of the back view of the embodiment shown in FIG. 3A.

FIG. 4A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 4B is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 4C is an illustration of the back view of the embodiment shown in FIG. 4A.

FIG. 4D is an illustration of an alternate back view of the embodiment shown in FIG. 4A.

FIG. 5A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 5B is an illustration of the back view of the embodiment shown in FIG. 5A.

FIG. 6A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 6B is an illustration of the back view of the embodiment shown in FIG. 6A.

FIG. 7A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention

FIG. 7B is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention

FIG. 7C is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention

FIG. 8A is a partial sectional view of another preferred embodiment of the reduced-size data card of the present invention taken through the tread where the tread includes raised dimples.

FIG. 8B is a partial sectional view of another preferred embodiment of the reduced-size data card of the present invention taken through the tread where the tread includes craters.

FIG. 9A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 9B is an illustration of the back view of the embodiment shown in FIG. 9A.

FIG. 9C is an illustration of a side view of the embodiment shown in FIG. 9A.

FIG. 10 is an illustration of the ISO/IEC 7811 standards for location and width of magnetic stripe data tracks 1 and 2.

FIG. 11 is an illustration of the ISO/IEC 7811 standards for location and width of magnetic stripe data track 3.

FIG. 12 is an illustration of the ISO/IEC 7811 standards for magnetic stripe location and size.

FIG. 13A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

FIG. 13B is an illustration of the back view of the embodiment shown in FIG. 13A.

DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings.

FIGs. 1A-B illustrate one embodiment of a conventional credit card. FIG. 1A shows the front side of a conventional standard size credit card 10, which is typically embossed using raised lettering with a credit card number 11, an expiration date 12, and the name of the card-holder 13. Such a card also usually contains the name of the issuing bank 14, and the credit card company, such as American Express®, MasterCard®, or VISA®, 15. It may also contain other information, such as sponsor logos and/or a "platinum" or similar indication. Additionally, the credit card may contain an identification photograph of the card-holder for security purposes. The back side of conventional card 10, shown in FIG. 1B, typically contains a box 16 that can be signed by the card holder, which is used for verification purposes when a purchase is made. Additionally, the back side of card 10 contains a magnetic stripe 17, which runs parallel to the card's largest dimension. Magnetic stripe 17 stores information, such as credit card number, that can be read by conventional point of sale ("POS") terminals. A standard credit card is approximately 3 3/8 in. long by 2 1/4 in. high, for an aspect ratio (length/height) of approximately 1.5, and has a thickness of approximately 0.75 mm.

The card of the present invention includes an information storage medium. By "information storage medium," is meant a medium that is added to the card that stores information in a magnetic, electronic, or electro-magnetic manner. This term does not include printed information either affixed to or printed directly on the card. Exemplary information storage media suitable for use with the present invention include, but are not limited to, magnetic stripes and computer chips.

FIGs. 2A-B depict a preferred embodiment of the present invention, including a generally rectangular card 20, a magnetic stripe 21, and a hole 22. The dimensions of card 20 are approximately 2 1/8 in. long by 1 1/4 in. high, for an aspect ratio (length/height) of approximately 1.7, and a thickness of approximately 0.75 mm. This is a significant reduction from the dimensions of a standard credit card. As would be appreciated by one skilled in the art, the foregoing specific dimensions are representative only, and the present invention is not limited to any particular dimensions. Preferably, the present invention is carried out using cards with dimensions ranging in length from approximately 1 in. to 3 in., and ranging in height from approximately 1 in. to 1 7/8 in. Thus, the aspect ratio (length/height) could range from approximately 0.53 (1 / 1.875) to 3 (3 / 1).

Magnetic stripe 21 is located on the back side of card 20, as shown in FIG. 2B, and is oriented perpendicularly to the card's largest dimension. Alternatively, the magnetic stripe could be located on the front side of card 20. In one embodiment of the present invention, magnetic stripe 21 is approximately 0.41 in. in width. In another embodiment, shown for example in FIGs. 3A-B, magnetic stripe 31 is approximately 0.25 in. in width.

ISO/IEC 7811 provides standards for the location of the stripe on the card, the surface profile of the stripe, and the height of the stripe above the card surface. Generally, designers of cards attempt to comply with these standards to ensure compatibility with existing POS terminals. Unexpectedly, the card of the present invention is compatible with existing point of sale terminals without complying with several aspects of the ISO/IEC standards, as explained in more detail below.

Finally, hole 22 is shown as located in a corner of card 20, and allows the card to be readily carried on a key-chain or like device. It should be apparent to one skilled in the art that hole 20 can be located anywhere on the card that allows the card to be carried by a key-chain or similar device and does not interfere with the magnetic stripe.

FIGs. 3A-B show an alternate preferred embodiment. Like the previous embodiment, this embodiment includes a generally rectangular card 30, a magnetic stripe 31, that is oriented perpendicularly to the card's largest dimension, and a hole 32. Here, however, magnetic stripe 31 is narrower in width than magnetic stripe 21 of FIG. 2B. A narrower magnetic stripe may be utilized when less information is needed to be stored by the magnetic stripe or when encoding techniques allow more information to be stored in a reduced space.

FIGs. 4A-D show alternate preferred embodiments. FIG. 4A shows a generally rectangular shaped card 40 with a hole 42. Card dimensions (2 1/8 in. by 1 1/4 in.) are shown on FIG. 4A and are significantly reduced from the standard size credit card. Additionally, card 40 contains an identification photograph 43, various logos 44 and 45, and additional information 46. Further, embossed information, such as credit card number or expiration date (not shown) could be included. Other arrangements of logos, and information should be apparent to one of ordinary skill in the art from this description or from practice. For example, FIG. 4B shows card 40 which is similar to card 40 (FIG. 4A) but without the identification photograph, and with a different arrangement of logos and other information.

FIG. 4C shows the back side of card 40, depicted in FIG. 4A, which includes magnetic stripe 41 oriented perpendicularly to the card's largest dimension. Additionally, FIG. 4C includes signature block 47. Signature block 47 is to be signed by the card holder, and is used for signature verification when a purchase is made. Finally, the back side of card 40 may contain logos 48 and other information, as would be apparent to one of ordinary skill in the art.

FIG. 4D shows an alternate arrangement of the back side of card 40. It shows magnetic stripe 41' which is narrower than magnetic stripe 41 of FIG. 4C. Narrower magnetic stripes may be utilized when less information is required to be stored by the magnetic stripe, or when encoding techniques allow more information to be stored in less space.

FIGs. 5A-B show an alternate preferred embodiment, including a generally rectangular shaped card 50 and a magnetic stripe 51, oriented perpendicularly to the card's largest dimension. Unlike previous embodiments, the present embodiment does not contain a hole. While a hole is a helpful way to attach a card of the present invention to a key-chain or like device, such a hole is not required. Thus, the card can be attached to the key-chain by a clip or similar device. Additionally, the card of the present invention is not required to be stored on a key-chain or like device and could be stored in any fashion chosen by the consumer, such as directly in the consumer's pocket or bag. It should be readily apparent to one skilled in the art that any of the embodiments described herein could be modified such that the hole is removed.

FIGs. 6A-B show still another alternate preferred embodiment, including a generally rectangular shaped card 60, a magnetic stripe 61, and a hole 62. Magnetic stripe 61 is oriented parallel to the card's largest dimension. As described above, magnetic stripe 61 is preferably compatible with existing magnetic stripe readers. Magnetic stripe 61 may be either narrow or wide, depending on the amount of data required to be stored and the degree of data compression. Because magnetic stripe 61 is oriented parallel to the card's longest dimension, it may be capable of storing a greater amount of information at a given width than magnetic stripe 21 of FIG. 2B which is oriented perpendicularly to the card's largest dimension. Thus, the present embodiment may be more easily implemented when greater amounts of information storage is required. It should be readily apparent to one of ordinary skill in the art that any of the embodiments described herein could be modified such that the magnetic stripe is oriented parallel to the card's largest dimension.

Conventional credit cards and the like have been generally rectangular in shape. However, the card of the present invention may take on other shapes. For example, the card could be any number of geometric shapes such as triangular or trapezoidal. Additionally, the card could take on the shape of naturally occurring or human-made objects, such as pine trees or airplanes. Such shapes could be related to the card issuer or sponsor. Thus, a credit card that a consumer can use to accrue frequent flier miles could be in the shape of an airplane. The dimensions of such cards generally comport with the size guidelines suggested herein. Because such cards are not rectangular, the magnetic stripe would not necessarily be oriented as described above (either parallel to or perpendicular to the card's largest dimension). Thus, the magnetic stripe could be oriented in any number of ways, depending on the shape of the card.

Additionally, any of the embodiments described herein could be provided with a tread to increase the gripability of the card. Such treads are described in detail in U.S. Patent Application No. 09/611,320 filed on July 6, 2000, the entirety of which is hereby incorporated by reference.

These treads could take the form of a plurality raised dimples disposed on a surface of the card. The treads are preferably disposed on the surface or face of the card that comes into contact with the user to increase gripability. FIGs. 7A-C show three alternate preferred embodiments of the present invention in which the surface of the card is provided with treads. In each a number of dimples 77 is arranged to form a plurality of treads 76 on the front face 71 of card 70. In FIG. 7A, the dimples 77 are arranged to form treads 76 in either a triangular pattern or a line. The dimples 77, however, can also be arranged in any number of patterns. As depicted in FIGs. 7A-7C, the treads 76 are located near an edge 73 of card 70, and in each preferred embodiment depicted in FIGs. 7A-7C, a tread 76 is located near the top edge 72 of the card 70. Other arrangements of dimples 77 forming treads 76 should be apparent to one of skill in the art from this description of from practice of the invention depending on the intended or experienced use of the card.

FIG. 8A shows a sectional view of a preferred embodiment of card 70 of the present invention taken along the line X-X of FIG. 7A, in which the dimples 77 are raised from the front face 71 of the card 70. In such an embodiment, the height of each dimple should be selected so as not to interfere with the proper operation of POS terminals or other devices that require the card to be swiped by or through the device.

FIG. 8B shows a sectional view of an alternate preferred embodiment of card 70 of the present invention. In this embodiment, the dimples are created in such a manner as to create individual craters 77 in which the lip of the crater is raised slightly above the front surface 71 of the card 70, while the center of the crater is slightly below the surface of the card.

While the specific embodiments described herein are cards having magnetic stripes such as credit cards, debit cards, and bank cards, this is by way of example, and the invention is not limited to these types of cards. Thus, the present invention can be implemented for many different types of data cards including Smart Cards (i.e. cards containing computer chips that store information), stored value cards, proximity chip cards, and other cards that are capable of storing information. A detailed discussion of data cards containing embedded computer chips may be found in U.S. Patent No. 4,443,027 to McNeely et al., the entirety of which is hereby incorporated by reference.

Another preferred embodiment of the present invention will now be described in greater detail. This preferred embodiment, shown in FIGs. 9A-C, includes a generally rectangular card 90, a magnetic stripe 91, and a hole 92. The front face 93 of card 90 is shown in FIG. 9A; the rear face 94 of card 90 is shown in FIG. 9B. Approximate dimensions of card 90, as indicated on FIG. 9B, are 1 9/16 inches (height) by 2 9/16 inches (length). The width of the card, shown in FIG. 9C (not to scale), is approximately 0.75 mm. These height and length dimensions are reduced from conventionally-sized credit card dimensions, which are approximately 2 1/4 inches (height) by 3 3/8 inches (length).

Once again, the specific dimensions of card 90 are representative only, and the present invention is not limited to any particular dimensions. Nevertheless, the present invention is preferably carried out using cards with dimensions ranging from approximately 1 inch by 1 inch to approximately 1 7/8 inches to 3 inches.

The front face 93 of card 90 contains various information such as card number 95, expiration date 96, and card-holder name 97. This information may be embossed on the card. In a preferred embodiment, the card is free from or devoid of embossing or other raised lettering. In such an embodiment, the information may be printed on the card using laser printing techniques, as are known in the art.

Between front and rear faces 93 and 94 of card 90 is a core 99, as shown in FIG. 9C. This core may be composed of, at least in part, polyester. In one embodiment, the core is composed of 80% polyester and 20% polyvinyl chloride (PVC). The use of polyester in the core is advantageous because it increases the durability of the card. As would be apparent to one skilled in the art, various percentages of polyester and other materials may be used for the card core.

In the embodiment shown in FIGs. 9A-C, magnetic stripe 91 is positioned parallel to the bottom edge 98 of card 90. The bottom edge, of course, is defined with respect to the particular card orientation shown in FIG. 9B. As would be readily apparent to one skilled in the art, rotation of card 90 could cause "bottom" edge 98 to appear as if it is a right, left, or top edge. Magnetic stripe 91 is used to store encoded data such as the name of the card-holder, a credit card or other account number, card expiration date, and a personal identification code or other security information. The lengthwise dimension of magnetic stripe 91 is approximately 2 9/16 inches. As defined herein, the lengthwise dimension of a magnetic stripe is the largest dimension of the magnetic stripe. However, as described above, the present invention is not limited to any particular dimensions. Preferably, the lengthwise dimension of the magnetic stripe ranges from approximately 1 inch to approximately 3 inches.

The requirements of ISO/IEC 7811, which specifies the international standards for magnetic stripes will now be discussed, and then compared to the characteristics of magnetic stripe 91 of the present invention. Designers of cards bearing magnetic stripes attempt to comply with the standards set forth in ISO/IEC 7811 in order to ensure compatibility and interoperability with current magnetic stripe readers and POS terminals.

ISO/IEC 7811 specifies that a magnetic stripe may contain up to three tracks of encoded information. As will be appreciated by one skilled in the art, each track is essentially a strip of specified width and location running the length of the magnetic stripe, on which data is encoded. According to ISO/IEC 7811, track 1 is located closest to the edge of the card and contains data encoded at 210 bits per inch (bpi). Track 2 is adjacent to track 1 and contains data encoded at 75 bpi. FIG. 10 shows the width and location of tracks 1 and 2 as specified by ISO/IEC 7811-4, the entirety of which is hereby incorporated by reference. Track 3 is the furthest from the edge of the card and contains data encoded at 210 bpi. FIG. 11 shows the

width and location of track 3 as specified by ISO/IEC 7811-5, the entirety of which is hereby incorporated by reference.

In all cases, data is encoded on the tracks using two-frequency encoding, as specified in ISO/IEC 7811. As will be understood by one skilled in the art, two-frequency encoding involves the use of flux transitions to encode data. The encoding comprises data and clocking transitions together. The presence of a flux transition between clocking transitions signifies that the bit is a "one;" the absence of a flux transition signifies a "zero." Additional detailed discussion of two-frequency encoding may be found in ISO/IEC 7811-2 and 7811-6, the entirety of which is incorporated herein by reference.

Each track of data contains a "start sentinel." The start sentinel is the first data bit, and indicates the beginning of the encoded data on each track. As shown in FIG. 12, ISO/IEC 7811 specifies that the location of the start sentinel is approximately 0.293 inches from the right side of the card for all tracks.

FIG. 12 shows additional physical characteristics for magnetic stripes, as specified by ISO/IEC 7811. The minimum length of the magnetic stripe is specified as 3.135 inches (3.250 inches minimum from the right edge of the card to the left edge of the stripe minus the 0.115 inches maximum from the right edge of the card to the right edge of the stripe). The minimum width of the magnetic stripe is 0.25 inches for cards using tracks 1 and 2, and 0.41 inches for cards using all three tracks.

Magnetic stripe 91 (FIG. 9B) is different in several respects from the magnetic stripes specified by ISO/IEC 7811. First, the length of magnetic stripe 91 is approximately 2 9/16 inches, significantly shorter than the 3.135 inch minimum length specified by ISO/IEC 7811.

Second, the data on magnetic stripe 91 is encoded at bit densities higher than those prescribed in ISO/IEC 7811. Magnetic stripe 91 contains data encoded on tracks 1 and 2. In order to ensure that sufficient data is encoded in the smaller magnetic stripe area, data is encoded on track 1 at 260 bpi and on track 2 at 100 bpi. Both of these bit densities are significantly higher than those specified in ISO/IEC 7811 for tracks 1 and 2 (210 bpi and 75 bpi, respectively). As should be appreciated by one skilled in the art, data could also be encoded on track 3 if necessary or desirable in a particular circumstance. It should also be noted that the

present invention is not limited by these specific bit densities, and other bit densities could be selected that ensure the storage of the appropriate amount of information in the available space.

Also, as shown in FIG. 9B, the start sentinel of magnetic stripe 91 is located 0.200 inches from the right edge of card 90. This start sentinel location is significantly different from that specified in ISO/IEC 7811, which specifies that the start sentinel must be located 0.293 inches from the right edge of the card.

Preferably, the data on tracks 1 and 2 of magnetic stripe 91 is encoded using standard two-frequency encoding. However, it should be understood by one skilled in the art that the present invention is not limited to a particular encoding technique. Preferably, the width of each track and the distance of each track from the bottom edge 98 of card 90 complies with the requirements of ISO/IEC 7811, as described above and shown in FIG. 10.

The dimensions of card 90 itself are different from the dimensions specified in ISO/IEC 7810, the entirety of which is hereby incorporated by reference, which generally specifies physical parameters of identification cards. Notably, ISO/IEC 7810 establishes minimum dimensions for identification cards at 2.125 inches by 3.370 inches. The dimensions of card 90 are approximately 1 9/16 inches by 2 9/16 inches.

Given that card 90 of the present invention does not comply with numerous standards and specifications set forth in ISO/IEC 7810 and 7811, it would be expected by those skilled in the art that the card would not be operable with standard magnetic stripe readers and POS terminals. However, tests performed on prototype cards indicate that the data cards of the present invention are compatible with standard equipment.

In order to test the prototype cards, twenty-five cards, substantially similar to that shown in FIGs. 9A and 9B and described above, were assembled and encoded with twenty-five different accounts. These twenty-five cards were then tested using five different POS terminals. The five POS terminals were standard merchant POS terminals manufactured by VeriFone Inc. A number of the twenty-five cards were tested on each of the five POS terminals. In order to ensure proper reading of the card, two tests were performed. First, after swiping each test card through the terminal, the terminal attempted to print a receipt showing, among other things, the name associated with the account encoded on each card. Second, the terminal used the data obtained from the card, and attempted to access the interchange system and obtain authorization

for a transaction. All tested cards passed both tests. This testing indicates that the data card of the present invention is unexpectedly compatible with POS terminals, despite the non-compliance with numerous aspects of ISO/IEC 7810 and 7811.

Additional testing was carried out using cards similar to card 130, shown in FIGs. 13A and 13B. Card 130 differs from card 90 only in that edge 139 of card 130 is angled. The same testing protocol described above was performed on twenty-five cards substantially similar to card 130 as shown in FIGs. 13A and B. The magnetic stripe 131 on card 130 is substantially the same as magnetic stripe 91 of card 90 (FIG. 9B). All cards tested passed both the receipt and authorization tests.

Thus, testing the prototype cards of various embodiments reveals that cards of the present invention are interoperable with magnetic card reader technology and POS terminals despite non-compliance with several of the relevant ISO/IEC standards.

Now will be described a method of use for a reduced-size data card of the present invention. As described above, such a card may be stored on a key-chain, lanyard, hook or similar device. Alternatively, the card may simply be placed in the pocket or bag of a consumer. When a consumer carrying a card of the present invention approaches a POS terminal or other card reader, such as when making sales transaction, the consumer may be required to produce the card to complete the transaction. Because of the convenience of storage, the consumer quickly and easily retrieves the card, and either gives the card to the merchant to "swipe" through the reader, or the consumer may be permitted to "swipe" the card him/herself. The POS terminal or other card reader then "reads" the encoded information on the card, such as card number, credit limit or the like, and the transaction is completed. The card may then be re-stored by the consumer until the next usage.

Although particular embodiments of the invention have been described and illustrated herein, it is recognized that modifications and variations may readily occur to those skilled in the art, and consequently it is intended that the claims be interpreted to cover such modifications and equivalents.

CLAIMS

1. A data card comprising a first face, a second face, and an information storage medium, wherein said card has dimensions that are less than about 2 1/4 inches by about 3 3/8 inches.
2. A data card as in claim 1, wherein the dimensions of said card are in the range of about 1 inch by about 1 inch to about 1 7/8 inches by about 3 inches.
3. A data card as in claim 1, wherein the information storage medium comprises a magnetic stripe.
4. A data card as in claim 3, wherein the magnetic stripe is positioned parallel to an edge of said card.
5. A data card as in claim 3, wherein the magnetic stripe is positioned perpendicular to a largest dimension of said card.
6. A data card as in claim 3, wherein the magnetic stripe comprises two tracks for storing encoded data.
7. A data card as in claim 6, wherein a first of said two tracks comprises data encoded at greater than about 210 bits per inch.
8. A data card as in claim 7, wherein the first of said two tracks comprises data encoded at about 260 bits per inch.
9. A data card as in claim 6, wherein a second of said two tracks comprises data encoded at greater than about 75 bits per inch.
10. A data card as in claim 9, wherein the second of said two tracks comprises data encoded at about 100 bits per inch.
11. A data card as in claim 6, wherein the encoded data is encoded using two-frequency encoding.

12. A data card as in claim 1, wherein said first and second faces define a hole therethrough.

13. A data card as in claim 1, further comprising a core disposed between said first and second faces, wherein said core comprises polyester.

14. A data card as in claim 13, wherein said core comprises about 80% polyester.

15. A data card as in claim 1, wherein the dimensions of said card are about 1 9/16 inches by about 2 9/16 inches.

16. A data card as in claim 1, wherein said first and second faces are devoid of raised lettering.

17. A data card as in claim 1, further comprising lettering printed on at least one of said first and second faces.

18. A data card as in claim 1, wherein the information storage medium comprises a computer chip.

19. A data card as in claim 1, further comprising a tread comprising a plurality of raised dimples for improving the gripability of said card, wherein said plurality of raised dimples are disposed on one of said first and second faces, said one face coming into contact with a user to improve gripability.

20. A data card as in claim 1, further comprising a plurality of craters disposed on one of said first and second faces, each of said plurality of craters comprising: a lip and a center, and wherein the lip of each crater is raised slightly above said one face, and the center of each crater is indented slightly into said one face.

21. A data card comprising a first face, a second face, and a magnetic stripe, wherein the magnetic stripe is positioned parallel to an edge of said card, and the magnetic stripe has a lengthwise dimension of less than about 3.135 inches.

22. A data card as in claim 21, wherein the lengthwise dimension of the magnetic stripe is in the range of about 1 inch to about 3 inches.

23. A data card as in claim 22, wherein the magnetic stripe comprises two tracks for storing encoded data.

24. A data card as in claim 23, wherein a first of said two tracks comprises data encoded at greater than about 210 bits per inch.

25. A data card as in claim 24, wherein the first of said two tracks comprises data encoded at about 260 bits per inch.

26. A data card as in claim 23, wherein a second of said two tracks comprises data encoded at greater than about 75 bits per inch.

27. A data card as in claim 26, wherein the second of said two tracks comprises data encoded at about 100 bits per inch.

28. A data card as in claim 23, wherein the encoded data is encoded using two-frequency encoding.

29. A data card as in claim 21, further comprising a core disposed between said first and second faces, wherein said core comprises polyester.

30. A data card as in claim 29, wherein the core comprises about 80% polyester.

31. A data card as in claim 21, wherein the lengthwise dimension of the magnetic stripe is about 2 9/16 inches.

32. A data card as in claim 21, wherein said first and second faces are devoid of raised lettering.

33. A data card as in claim 21 further comprising lettering printed on at least one of said first and second faces.

34. A data card as in claim 21 further comprising a tread comprising a plurality of raised dimples for improving the gripability of said card,

wherein said plurality of raised dimples are disposed on one of said first and second faces, said one face coming into contact with a user to improve gripability.

35. A data card as in claim 21, further comprising a plurality of craters disposed on one of said first and second faces, each of said plurality of craters comprising: a lip and a center, and wherein the lip of each crater is raised slightly above said one face, and the center of each crater is indented slightly into said one face.

36. A data card as in claim 21, wherein said first and second faces define a hole therethrough.

37. A data card as in claim 21, further comprising an angled edge.

38. A data card comprising a first face, a second face, an angled edge, and an information storage medium, wherein a largest dimension of said card is less than about 3 3/8 inches.

39. A data card as in claim 38, wherein the largest dimension of said card is in the range of about 1 7/8 inches to about 3 inches.

40. A data card as in claim 38, wherein the information storage medium comprises a magnetic stripe.

41. A data card as in claim 40, wherein the magnetic stripe is positioned parallel to an edge of said card.

42. A data card as in claim 41, wherein the magnetic stripe comprises two tracks for storing encoded data.

43. A data card as in claim 42, wherein a first of said two tracks comprises data encoded at greater than about 210 bits per inch.



44. A data card as in claim 43, wherein the first of said two tracks comprises data encoded at about 260 bits per inch.

45. A data card as in claim 42, wherein a second of said two tracks comprises data encoded at greater than about 75 bits per inch.
46. A data card as in claim 45, wherein the second of said two tracks comprises data encoded at about 100 bits per inch.
47. A data card as in claim 42, wherein the encoded data is encoded using two-frequency encoding.
48. A data card as in claim 38, wherein said first and second faces define a hole therethrough.
49. A data card as in claim 38, further comprising a core disposed between said first and second faces, wherein said core comprises polyester.
50. A data card as in claim 49, wherein said core comprises about 80% polyester.
51. A data card as in claim 38, wherein said first and second faces are devoid of raised lettering.
52. A data card as in claim 38, further comprising lettering printed on at least one of said first and second faces.
53. A data card as in claim 38, wherein the information storage medium comprises a computer chip.
54. A data card as in claim 38, further comprising a tread comprising a plurality of raised dimples for improving the gripability of said card, wherein said plurality of raised dimples are disposed on one of said first and second faces, said one face coming into contact with a user to improve gripability.
55. A data card as in claim 38, further comprising a plurality of craters disposed on one of said first and second faces, each of said plurality of craters comprising: a lip and a center, and wherein the lip of each crater is raised slightly above said one face, and the center of each crater is indented slightly into said one face.

56. A data card as in claim 40, wherein the magnetic stripe is positioned perpendicular to the largest dimension of said card.

57. A data card as in claim 40, wherein the magnetic stripe is positioned parallel to said angled edge.

1/10

**FIG. 1A****FIG. 1B**

SUBSTITUTE SHEET (RULE 26)




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C







FIG. 4D

4/10

50


**FIG. 5A**

51

FIG. 5B

62

60




FIG. 6A

61

FIG. 6B



SUBSTITUTE SHEET (RULE 26)

5/10

**FIG. 7A****FIG. 7B****FIG. 7C**

SUBSTITUTE SHEET (RULE 26)

6/10

**FIG. 8A****FIG. 8B**

7/10




FIG. 9A




FIG. 9B







FIG. 9C

SUBSTITUTE SHEET (RULE 26)



8/10

*FIG. 10**FIG. 11*


9/10

**FIG. 12**

10/10

**FIG. 13A****FIG. 13B**

2 Arten von Karten



2.1	Hochgeprägte Karten	44
2.2	Magnetstreifenkarten	45
2.3	Chipkarten.....	47
2.3.1	Speicherkarten	48
2.3.2	Mikroprozessorkarten	50
2.3.3	Kontaktlose Chipkarten.....	51
2.4	Optische Speicherkarten.....	54

Wie bereits in der Einleitung erwähnt, sind die Chipkarten das jüngste Kind der Familie der Identifikationskarten im ID-1 Format, wie sie in der Norm ISO 7810 „Identification Cards – Physical Characteristics“ definiert sind. Diese Norm spezifiziert die physikalischen Eigenschaften von Identifikationskarten einschließlich der Materialeigenschaften wie Flexibilität, Temperaturbeständigkeit und Abmessungen für drei verschiedene Größen von Karten (ID-1, ID-2 und ID-3). Die Basis für die Chipkartennormen ISO 7816-1 ff bildet die ID-1 Karte, wie sie heute millionenfach als Karte für den Zahlungsverkehr verbreitet ist.

Dieses Kapitel gibt einen Überblick über verschiedene Arten von Karten im ID-1 Format. In vielen Anwendungen ist nämlich eine Kombination der Kartenfunktionen von besonderem Interesse, und zwar immer dann, wenn in einem bereits bestehenden System die vorhandenen Karten, wie z.B. Magnetstreifenkarten, durch Chipkarten abgelöst werden sollen. In der Regel ist es nämlich unmöglich, die vorhandene Infrastruktur – in diesem Falle die Terminals für Magnetstreifenkarten – von heute auf morgen durch eine neue Technik zu ersetzen.

Die Lösung wird im allgemeinen darin bestehen, daß man für eine Übergangszeit Karten ausgibt, die mit Magnetstreifen und mit Chip ausgerüstet sind, so daß die Karten sowohl an den alten Magnetkartenterminals wie auch an den neuen Chipkartenterminals benutzt werden können. Neue Funktionen, die nur mit dem Chip möglich sind, können dann natürlich an den Magnetkartenterminals nicht genutzt werden.

2.1 Hochgeprägte Karten

Die Hochprägung ist die älteste Technik zur Beschriftung von Identifikationskarten in maschinenlesbarer Form. Die hochgeprägten Zeichen auf der Karte können mit einem einfachen und billigen Gerät durch Abdruck auf Papier übertragen werden. Auch das visuelle Lesen der Hochprägung ist ohne weiteres möglich. Die Art und Lage der Hochprägung ist im Standard ISO 7811 „Identification Cards – Recording Technics“ spezifiziert. Dieser Standard besteht aus fünf Teilen und behandelt außer der Hochprägung auch den Magnetstreifen.

In ISO 7811, Teil 1 sind die Anforderungen an hochgeprägte Zeichen, wie deren Form, Größe und Prägehöhe, spezifiziert.

Im Teil 3 wird die genaue Lage der Zeichen auf der Karte festgelegt, und zwar sind zwei verschiedene Bereiche definiert. Der Bereich 1 ist für die Kartenidentifikationsnummer reserviert, durch welche der Kartenausgeber sowie der Karteninhaber festgelegt sind. Der Bereich 2 ist für weitere Daten des Karteninhabers wie z.B. Name und Adresse vorgesehen.

Auf den ersten Blick mag die Informationsübertragung durch Abdruck hochgeprägter Zeichen recht primitiv erscheinen. Die Einfachheit dieser Technik hat jedoch ihre weltweite Verbreitung auch in unterentwickelten Ländern der Erde ermöglicht. Die Anwendung dieser Technik erfordert weder elektrische Energie noch Anschluß an das Telefonnetz.




Bild 2.1

Lage der Hochprägung nach ISO 7811-3. Der Bereich 1 ist für die Identifikationsnummer (19 Zeichen) vorgesehen. Der Bereich 2 für Name und Adresse (4 · 27 Zeichen). Die folgenden Abmessungen sind in der Norm festgelegt:

A: 21,42 mm ± 0,12 mm	B: 10,18 mm ± 0,25 mm
D: 14,53 mm	E: 2,41 mm ... 3,30 mm
F: 7,65 mm ± 0,25 mm	

2.2 Magnetstreifenkarten

Der wesentliche Nachteil der hochgeprägten Karten liegt darin, daß bei ihrer Nutzung eine Flut von Papierbelegen entsteht, deren Handhabung und Auswertung hohe Kosten verursacht. Abhilfe schafft hier die digitale Codierung der Kartendaten auf einem Magnetstreifen, der sich auf der Rückseite der Karte befindet.

Zum Lesen des Magnetstreifens wird dieser von Hand oder maschinell an einem Lesekopf vorbeigezogen, wobei die Daten gelesen und elektronisch gespeichert werden. Zur Bearbeitung dieser Daten ist dann kein Papier mehr erforderlich.

In den Teilen 2, 4 und 5 der ISO-Norm 7811 sind die Eigenschaften des Magnetstreifens, die Codiertechnik sowie die Lage der Magnetspuren spezifiziert. Insgesamt können sich drei Spuren auf dem Magnetstreifen befinden.

Die Spuren 1 und 2 sind nur für den Lesebetrieb spezifiziert, während die Spur 3 auch beschrieben werden kann.




Bild 2.2 Die Lage des Magnetstreifens auf der ID-1 Karte. Der Datenbereich des Magnetstreifens reicht bewußt nicht bis zu den Kartenkanten, da die handbedienten Magnetstreifenleser dort zu einer sehr frühzeitigen Abnutzung des Magnetstreifens führen.

Die Speicherkapazität des Magnetstreifens ist allerdings mit ca. 1 000 Bit nicht sehr groß. Sie reicht jedoch leicht aus, um die Informationen der Hochprägung zu speichern. Auf der Spur 3 können zusätzliche Daten gelesen und geschrieben werden, wie z.B. Daten der letzten Transaktion bei Kreditkarten.




Bild 2.3 Die Lage der einzelnen Spuren auf der ID-1 Karte. Alle Maße sind in Millimeter angegeben.

Der Hauptnachteil der Magnetstreifentechnik besteht darin, daß die gespeicherten Daten sehr leicht verändert werden können. Während die Manipulation an hochgeprägten Zeichen zumindest einiges handwerkliches Geschick erfordert und von einem geschulten Auge auch leicht entdeckt werden kann, ist die Veränderung der auf der Magnetpiste kodierte Daten mit einem handelsüblichen Schreib-/Lesegerät problemlos möglich und später nur schwer nachweisbar. Hinzu kommt noch, daß die Magnetstreifenkarte häufig in Automaten zum Einsatz kommt, an denen eine visuelle Echtheitsprüfung unmöglich ist, wie z.B. in Geldausgabeautomaten. Der potentielle Betrü-

ger, der sich gültige Kartendaten verschafft hat, kann an solchen unbemannten Automaten einfache Duplikate von Karten verwenden, ohne daß er die visuellen Sicherheitsmerkmale fälschen muß.

Die Hersteller von Magnetstreifenkarten haben verschiedene Techniken entwickelt, um die Daten auf der Magnetpiste gegen Verfälschen und Duplizieren zu schützen. So sind z.B. die deutschen Eurocheque-Karten mit einer unsichtbaren und unveränderbaren Codierung im Kartenkörper versehen, die eine Veränderung der Daten auf der Magnetpiste sowie ein Duplizieren unmöglich macht. Dieses und andere Verfahren erfordern allerdings einen speziellen Sensor im Kartenterminal, wodurch deren Kosten deutlich erhöht werden. Deshalb konnte sich bisher keines dieser Verfahren international durchsetzen.

Tabelle 2.1 Die einzelnen Spuren einer Magnetstreifenkarte mit ihren üblichen Eigenschaften nach ISO 7811.

Eigenschaft	Spur 1	Spur 2	Spur 3
Anzahl der Daten	max. 79 Zeichen	max. 40 Zeichen	max. 107 Zeichen
Codierung der Daten	6 Bit alpha-numerischer Code	4 Bit BCD Code	4 Bit BCD Code
Datendichte	210 Bit/inch = 8,3 Bit/mm	75 Bit/inch = 3 Bit/mm	210 Bit/inch = 8,3 Bit/mm
Schreibbar	nicht erlaubt	nicht erlaubt	erlaubt

2.3 Chipkarten

Die Chipkarte ist das jüngste und schlaueste Kind in der Familie der Identifikationskarten im ID-1 Format. Es zeichnet sich dadurch aus, daß im Kartenkörper eine integrierte Schaltung versteckt ist, die über Elemente zur Datenübertragung, zum Speichern von Daten und zur Verarbeitung von Daten verfügt. Die Datenübertragung kann dabei entweder über die Kontakte an der Oberfläche der Karte erfolgen, oder aber kontaktlos durch elektromagnetische Felder.

Die Chipkarte bietet gegenüber der Magnetstreifenkarte eine Reihe von Vorteilen. So ist z.B. die maximale Speicherkapazität von Chipkarten um ein vielfaches größer als bei Magnetstreifenkarten. Heute werden bereits Schaltkreise mit mehr als 32 kByte Speicher angeboten, und dieser Wert wird sich mit jeder neuen Chipgeneration noch vervielfachen. Nur die im nächsten Kapitel beschriebenen optischen Speicherkarten haben eine noch größere Kapazität.

Einer der wichtigsten Vorteile der Chipkarte liegt jedoch darin, daß die in ihr gespeicherten Daten gegen unerwünschten Zugriff und gegen Manipulation geschützt werden können. Da der Zugriff auf die Daten nur über eine serielle Schnittstelle erfolgt, die vom Betriebssystem und einer Sicherheitslogik gesteuert wird, ist es möglich, geheime Daten in die Karte zu laden, die niemals mehr von außen gelesen werden können. Diese geheimen Daten können dann nur noch intern vom Rechenwerk des Chips verarbeitet werden. Grundsätzlich können die Speicherfunktionen Schreiben, Löschen und Lesen sowohl per Hardware als auch per Software eingeschränkt und an bestimmte

3 Physikalische und elektrische Eigenschaften

3.1	Physikalische Eigenschaften	56
3.1.1	Formate	57
3.1.2	Kartenelemente und Sicherheitsmerkmale	61
3.2	Kartenkörper	67
3.2.1	Kartenmaterialien	68
3.2.2	Chipmodule	71
3.3	Elektrische Eigenschaften	81
3.3.1	Beschaltung	81
3.3.2	Versorgungsspannung	82
3.3.3	Versorgungsstrom	84
3.3.4	Taktversorgung	85
3.3.5	Datenübertragung	86
3.3.6	An-/Abschaltsequenz	86
3.4	Mikrocontroller für Chipkarten	88
3.4.1	Prozessortypen	91
3.4.2	Speicherarten	93
3.4.3	Zusatzhardware	104

Die grundlegenden Eigenschaften des Kartenkörpers von Chipkarten stammen von den Vorgängern dieser Karten. Dies sind die seit langem bekannten Prägekarten, die vor allem im Kreditkartensektor momentan immer noch marktbeherrschend sind. Technisch gesehen sind sie einfach aufgebaute Karten aus Kunststoff, die durch Einprägung von diversen Benutzermerkmalen wie Name und Kundennummer personalisiert sind.

In weiterentwickelten Ausführungen wurden die Karten dann mit einem Magnetstreifen versehen, der so die einfache maschinelle Verarbeitung ermöglichte. Als dann die Idee aufkam, Karten mit einem Chip auszustatten, verwendete man die ursprünglichen Karten als Grundlage und implantierte zusätzlich noch einen Mikrocontroller. Viele Normen über die physikalischen Eigenschaften einer Karte sind gar nicht spezifisch für Chipkarten, sondern decken ebenfalls auch noch Magnetstreifen- und Prägekarten ab.

3.1 Physikalische Eigenschaften

Nimmt man eine Chipkarte in die Hand, dann ist das unmittelbar auffallende Merkmal das Format der Karte. Danach sieht man vielleicht, ob die Karte mit einem Kontaktfeld ausgestattet ist, obwohl manchmal überhaupt keine sichtbare elektrische Schnittstelle vorhanden ist (kontaktlose Chipkarte). Magnetstreifen, Hochprägung und Hologramm fallen eventuell als nächstes ins Auge. Alle diese Merkmale und Funktionsteile sind Teil der physikalischen Eigenschaften einer Chipkarte.

Ein Großteil der physikalischen Eigenschaften sind in Wahrheit rein mechanischer Natur, wie Größe, Biege- und Torsionsfestigkeit. Diese kennt man auch im praktischen

Umgang mit Chipkarten unmittelbar aus der Erfahrung. In der Praxis spielen jedoch sehr wohl typische physikalische Eigenschaften, wie Temperatur-, Lichtempfindlichkeit oder Feuchtebeständigkeit eine Rolle.

Man muß auch immer das Zusammenwirken von Kartenkörper und implantierten Chip betrachten, da nur beide miteinander eine funktionsfähige Chipkarte bilden. Ein Kartenkörper, der beispielsweise für sehr hohe Umgebungstemperatur geeignet ist, nützt wenig, wenn dies nicht auch der Mikrocontroller ist. Beide Teile müssen sowohl einzeln als auch miteinander alle notwendigen Anforderungen erfüllen, da es sonst zu hohen Ausfallraten beim Einsatz kommen kann.

3.1.1 Formate

Es wurden schon sehr lange kleine Kärtchen in der typischen Chipkartengröße von 85,6 mm Länge und 54 mm Breite verwendet. In diesem Format, das mit Sicherheit auch das bekannteste ist, werden fast alle Chipkarten produziert. Es hat die Bezeichnung ID-1 und ihre Größe ist in der internationalen Norm ISO 7810 festgelegt. Anhand der Abkürzung „ID“, die für Identifikationskarte steht, sieht man deutlich, daß diese erste Norm aus dem Jahre 1985 noch nichts mit den Chipkarten, wie wir sie heute kennen, zu tun hatte. Dort wird lediglich eine Kunststoffkarte mit einem Magnetstreifen und Hochprägung beschrieben, die zur Identifizierung von Personen dient. An einen in die Karte eingebauten Chip war damals noch nicht gedacht. Erst einige Jahre später definierte man in weiteren Normen das Vorhandensein eines Chips und die Position seiner Kontaktflächen auf der Karte.

Bei der heutigen Vielfalt an Karten, die für alle möglichen Zwecke verwendet werden und die verschiedenste Abmessungen haben, ist es mittlerweile oft schwierig festzustellen, ob eine Karte nun eigentlich eine ID-1 Chipkarte ist oder nicht. Eines der besten Erkennungsmerkmale ist neben dem implantierten Chip die Dicke der Karte. Beträgt die Dicke einer Karte mit implantiertem Mikrocontroller 0,76 mm, kann man im eigentlichen Sinne von einer Chipkarte nach ISO-Norm sprechen.





Bild 3.1

Das ID-1 Format. Dicke: 0,76 mm \pm 0,08 mm, Radius der Ecken: 3,18 mm \pm 0,30 mm. Die eingezeichneten Abmessungen stellen die Maße ohne Toleranzen dar.

Das gebräuchliche ID-1 Format hat den Vorteil, daß es manuell sehr gut handhabbar ist. Das Format der Karte ist so festgelegt, daß man sie in einer üblichen Geldbörse mit sich führen kann und ist aber nicht zu klein, als daß man sie leicht verlieren könnte. Außerdem ist sie wegen ihrer Flexibilität weniger störend, als ein Gegenstand, der steif ist.

Allerdings entspricht das Format oft nicht mehr den Erfordernissen der heutigen Miniaturisierung. Tragbare Telefone sind zum Teil nur mehr 100 g schwer und nicht viel größer als eine Packung Papiertaschentücher. Deshalb war es notwendig, neben ID-1 ein kleineres Format zu definieren, das die Belange der kleinen Endgeräte berücksichtigt. Die Karte durfte dabei sehr klein sein, da sie üblicherweise nur ein einziges Mal in das Endgerät gesteckt werden muß und dann dort für immer bleibt. Unter diesen Voraussetzungen definierte man das ID-000 Format, dessen einprägsamere Bezeichnung „Plug-In“ oder in deutsch „Einschubkarte“ lautet. Dieses Format kommt momentan nur im GSM-Bereich in Endgeräten zum Einsatz, in denen mechanisch sehr wenig Platz ist und in denen die Karte nicht öfter gewechselt werden muß.

Da jedoch die Handhabung der ID-000 Karte sowohl in der Fertigung als auch bei den Benutzern nicht gerade einfach ist, führte dies zu einem weiteren Format. Benannt ist dieses Format als ID-00 bzw. „Mini-Karte“. Es stellt in der Größe ungefähr den Mittelwert zwischen ID-1 und ID-000 dar. Dadurch läßt sich die Karte einfacher manuell handhaben und ermöglicht auch eine kostengünstigere Fertigung, weil sie sich besser bedrucken läßt. Die Definition von ID-00 ist allerdings ziemlich neu, und dieses Kartenformat hat sich zur Zeit weder national noch international etabliert.



13.2 Die Definition der Maße des ID-1 Formats für Chipkarten.

Die Definition der Formate in den jeweiligen Normen wurde auf meßtechnische Bedürfnisse hin optimiert. So muß ein Kartenkörper im Format ID-1 in seiner Höhe und Breite so beschaffen sein, daß er ohne die abgerundeten Ecken innerhalb zweier konzentrischer und symmetrisch zueinander angeordneter Rechtecke mit den folgenden Abmessungen paßt:

Äußeres Rechteck:	Breite 85,72 mm (= 3,375 inch)
	Höhe 54,03 mm (= 2,127 inch)
Inneres Rechteck:	Breite 85,46 mm (= 3,365 inch)
	Höhe 53,92 mm (= 2,123 inch)

Die Dicke muß 0,76 mm (= 0,03 inch) mit einer Toleranz von $\pm 0,08$ mm ($= \pm 0,003$ inch) betragen. Die Radien der Ecken und die Dicke des Kartenkörpers sind auf konventionelle Art bemaßt. Aufgrund dieser Definitionen kann man die Abmessungen einer ID-1 Karte in dem Bild 3.1 darstellen.

Dem ID-000 Format dienen ebenfalls zwei konzentrische Rechtecke als Grundlage der Formatdefinition. Da dieses Format seine Ursprünge in Europa hat (Grundlage war das Mobiltelefonsystem GSM), basiert es auf metrischen Grundmaßen. Die Abmessungen der beiden Rechtecke sind:

Äußeres Rechteck:	Breite 25,10 mm
	Höhe 15,10 mm
Inneres Rechteck:	Breite 24,90 mm
	Höhe 14,90 mm

Die rechte untere Ecke des Plug-In ist im Winkel von 45° abgetrennt, um damit die Orientierung der Karte beim Einlegen in den Kartenleser zu vereinfachen.




Bild 3.3

Das ID-000 Format. Dicke: $0,76 \text{ mm} \pm 0,08 \text{ mm}$, Radius der Ecken: $1 \text{ mm} \pm 0,10 \text{ mm}$, Ecke: $3 \text{ mm} \pm 0,03 \text{ mm}$. Die eingezeichneten Abmessungen stellen die Maße ohne Toleranzen dar.




Bild 3.4 Das ID-00 Format. Dicke: $0,76 \text{ mm} \pm 0,08 \text{ mm}$, Radius der Ecken: $3,18 \text{ mm} \pm 0,30 \text{ mm}$. Die eingezeichneten Abmessungen stellen die Maße ohne Toleranzen dar.

Das ebenfalls auf metrischen Grundmaßen basierende ID-00 Format ist gleichfalls in seinen Maximal- und Minimalgrößen durch zwei konzentrische Rechtecke definiert. Die Abmessungen dieser beiden Rechtecke sind:

Äußeres Rechteck:	Breite 66,10 mm
	Höhe 33,10 mm
Inneres Rechteck:	Breite 65,90 mm
	Höhe 32,90 mm




Bild 3.5 Die Zusammenhänge zwischen den Kartenformaten ID-1, ID-00 und ID-000.



Bild 3.6 Beispiel für eine GSM-Karte im ID-1 Format, die vom Kunden durch Auftrennen dreier Stege in das ID-000 überführt werden kann. (Giesecke und Devrient)

Die drei Formate ID-1, ID-00 und ID-000 können von den größeren Kartenkörpern zu den kleineren durch Stanzen überführt werden. Dies ist vor allem für die Kartenhersteller interessant, da sich damit der Fertigungsprozeß sehr gut optimieren und kostengünstiger gestalten läßt.

So ist es zum Beispiel denkbar, daß ein Hersteller nur Karten in einem einzigen Format (vorzugsweise ID-1) produziert, dann die Module einbettet und komplett personalisiert. Abhängig vom genauen Einsatzgebiet der so hergestellten Chipkarten können diese dann in einem nachgeordneten Produktionsschritt auf das gewünschte Format gebracht werden.

Alternativ dazu kann dies auch der Kunde machen, wie es im GSM-Bereich zum Teil schon durchgeführt wird. Der Kunde erhält eine ID-1 Karte, die vorgestanzt ist, so daß man durch Auftrennen von drei Bruchlaschen eine ID-000 Karte erhält. In einem anderen Verfahren ist die ID-000 komplett aus der ID-1 ausgestanzt und auf der den Kontakten abgewandten Seite durch ein einseitiges Klebeband mit dem restlichen Kartenkörper der ID-1 Karte verbunden. Damit kann der Kunde je nach vorhandenem Endgerät sein Kartenformat selber herstellen, und die Produktion und der Versand bleiben bei den Kartenherstellern ohne Varianten.

3.1.2 Kartenelemente und Sicherheitsmerkmale

Da Chipkarten meist als Berechtigungen für bestimmte Dinge oder zur Identifizierung des Inhabers genutzt werden, sind oft zusätzlich zu dem implantierten Chip noch Sicherheitsmerkmale auf dem Kartenkörper vonnöten. Da eine Kartenechtheitsprüfung auch durch Menschen und nicht nur durch Maschinen durchgeführt wird, beruhen viele Sicherheitsmerkmale auf optischen Merkmalen. Es gibt allerdings auch Sicherheitsmerkmale, die auf einem modifizierten Chipkarten-Mikrocontroller beruhen und deshalb nur durch Computer prüfbar sind. Die üblichen Merkmale für die manuelle Echtheitsprüfung einer Karte basieren im Gegensatz zu denen des Mikrocontrollers nicht auf kryptografischen Verfahren (z.B.: gegenseitige Authentisierung). Grundlage ist größtenteils die Geheimhaltung von Materialien und Herstellungsverfahren oder die Benutzung von technischen Verfahren, die nur mit sehr großem Aufwand, erheblichem Know-how oder technisch schwierig zu beherrschen sind.

Unterschriftsstreifen

Ein eher einfaches Verfahren zur Identifizierung des Besitzers ist ein fest mit dem Kartenkörper verbundener Unterschriftsstreifen, wie er z.B. auf Kreditkarten üblich ist. Einmal beschrieben, kann er nicht mehr geändert werden, ist also radierfest. Ein Überkleben des Streifens würde durch einen sehr feinen Farbdruk sofort sichtbar. Die irreversible Befestigung des Unterschriftsstreifens wird durch ein Heißklebeverfahren für den bedruckten Papierstreifen gewährleistet. Bei einem anderen Verfahren ist der Unterschriftsstreifen ein Teil der obersten Schicht des Kartenkörpers und wird beim Zusammenbau einlaminiert.

Guillochen

Etwas aufwendiger sind unter der transparenten obersten Schicht der Karte eingefügte Folien mit farbig aufgedruckten Guillochen. Als Guillochen werden die meist runden oder ovalen geschlossenen und miteinander verwobenen Linienfelder bezeichnet, die sich auch auf vielen verschiedenen Geldscheinen oder Aktien befinden. Diese Muster können aufgrund ihrer feinen Struktur momentan nur auf drucktechnischem Wege erzeugt werden und sind deshalb ebenfalls nicht kopierbar.

- Elektrostatische Entladungen
- Temperaturbeständigkeit

Im ISO-Standard ISO/IEC 10 373 sind für viele dieser Forderungen Testmethoden festgelegt, die dem Anwender und Hersteller von Karten eine objektive Prüfung der Kartenqualität ermöglichen. Für Chipkarten sind dabei die Biege- und Torsionstests von besonderer Wichtigkeit. Der Chip ist nämlich wegen seiner Materialeigenschaften (spröde und zerbrechlich wie Glas) ein empfindlicher Fremdkörper in der elastischen Karte und muß durch besondere konstruktive Maßnahmen gegen mechanische Beanspruchung bei Biegung und Torsion der Karte geschützt werden. In Kapitel 9 befindet sich eine detaillierte Aufstellung von Tests und dazu angewandter Methoden.




Bild 3.9 Die Systematik der Kartenelemente.

3.2.1 Kartenmaterialien

Das als erstes und auch heute noch am meisten verwendete Material für Identifikationskarten ist der amorphe Thermoplast PVC (Polyvinylchlorid). Es ist das preisgünstigste aller verfügbaren Materialien, läßt sich gut verarbeiten und deckt ein weites Einsatzspektrum ab. So kommt es beispielsweise weltweit bei Kreditkarten zum Einsatz. Nachteile von PVC sind die begrenzte Lebensdauer wegen der Alterung des Materials sowie die geringe Temperaturbeständigkeit. Als Ausgangsmaterial für die Kartenkörperproduktion wird PVC als Folie verwendet, der Spritzguß von PVC ist nicht

möglich. Die weltweite Produktion an PVC betrug im Jahr 1996 ungefähr 13 Millionen Tonnen, davon entfielen 35 000 Tonnen auf Karten, was einem Anteil von ca. 0,27 % entspricht. PVC gilt allgemein als umweltschädlich. So ist der Ausgangsstoff Vinylchlorid als krebserregend eingestuft, und bei der Verbrennung kann Salzsäure und unter ungünstigen Bedingungen sogar Dioxin entstehen. Weiterhin enthält PVC zur Stabilisierung oft Schwermetalle. Allerdings ist PVC noch immer mit Abstand der am häufigsten benutzte Kunststoff für Karte. Dies ist vor allem durch den Preis und die gute Verarbeitbarkeit begründet. Aufgrund der schlechten Umwelteigenschaften sinkt aber der Einsatz von PVC von Jahr zu Jahr. Viele Kartenherausgeber lehnen mittlerweile dieses Material aus umweltpolitischen Erwägungen prinzipiell ab.

Um die Nachteile von PVC zu umgehen, werden seit einiger Zeit Karten aus ABS (Acrylnitril-Butadien-Styrol) gefertigt. Dieses Material ist ebenfalls ein amorpher Thermoplast und zeichnet sich durch hohe Festigkeit und Temperaturbeständigkeit aus. Deshalb ist ABS das üblicherweise bei Mobilfunkkarten eingesetzte Material, die aus naheliegenden Gründen sehr hohen Temperaturbelastungen ausgesetzt sind. ABS läßt sich sowohl als Folie als auch im Spritzguß gut verarbeiten. Die Hauptnachteile dieses Materials sind seine eingeschränkte Farbgebung sowie die Empfindlichkeit gegen Witterungseinflüsse. Der Ausgangsstoff Benzol ist krebserregend, doch sonst sind keine die Umwelt betreffenden Nachteile bekannt.




Bild 3.10 Strukturformeln der wichtigsten Kunststoffe für Kartenkörper.

Für Anwendungen, bei denen hohe Festigkeit und Langlebigkeit gefordert ist, wird Polycarbonat (PC) eingesetzt. Es ist ein typisches Material für Ausweiskarten und am Rande bemerkt auch das Trägermaterial für CDs. Aufgrund der guten Wärmebeständigkeit von Polycarbonat benötigt man zum Aufbringen von Hologrammen oder Magnetstreifen im Hot-Stamp-Verfahren relativ hohe Temperaturen, was leicht zu Problemen mit der Temperaturbeständigkeit des aufzubringenden Materials führen kann. Die Hauptnachteile von Polycarbonat sind die Kerbempfindlichkeit sowie der gegenüber allen anderen Kartenmaterialien sehr hohe Preis. Ungünstigerweise sind für die Herstellung von Polycarbonat die beiden umwelttechnisch bedenklichen Stoffe Phosgen und Chlor vonnöten. Polycarbonatkarten lassen sich sehr leicht erkennen, indem man sie auf einen harten Untergrund fallen läßt und es „blechern“ klingt.

Ein umweltfreundliches Ersatzmaterial vor allem für PVC, das im Verpackungsbereich schon seit längerer Zeit eingesetzt wird, ist Polyethylenterephthalat (PET), dessen umgangssprachlicher Name Polyester lautet. Dieser thermoplastische Kunststoff wird bei Chipkarten sowohl in seiner amorphen (A-PET) als auch in der teilkristallinen (PETP) Form verwendet. Beide eignen sich sowohl für Folien- als auch für Spritzgußverarbeitung. Allerdings läßt sich das teilkristalline PET schwierig laminieren, was zusätzliche Arbeitsschritte bei der Fertigung notwendig macht.

Tabelle 3.1 Die üblichen Materialien für Kartenkörper und ihre Eigenschaften im Überblick.¹ Die Preise sind relativ zu PVC angegeben.

Eigenschaften	PVC	ABS	PC	PET
Haupteinsatz	Kreditkarten	Mobiltelefonkarten	ID-Karten	KV-Karten
Haupteigenschaft	kostengünstig	temperaturbeständig	langlebig	umweltfreundlich
Kartenherstellung	nur Folie	Folie und Spritzguß	Folie und Spritzguß	Folie und Spritzguß
Wärmebeständigkeit	65 – 90 °C	75 – 100 °C	160 °C	bis 80 °C
Kältebeständigkeit	mittel	hoch	mittel	mittel
mechanische Festigkeit	gut	gut	gut	sehr gut
Embossing	gut	schlecht	gut	gut
Bedrucken	gut	mittel	mittel	gut
Hot-Stamping (z.B.: für Hologramme u.ä.)	gut	gut	schwierig	gut
Lasergravur	ja	schlecht	gut	gut
typ. Lebensdauer	ca. 2 Jahre	ca. 3 Jahre	ca. 5 Jahre	ca. 3 Jahre
Anteil an der weltweiten Kartenproduktion (1998)	85 %	8 %	5 %	2 %
Preis	1 fach	2 fach	7 fach	2,5 fach
Umwelt	<ul style="list-style-type: none"> • u.U. Bildung von Dioxin bei Verbrennung • Stabilisatoren aus Schwermetallen 	<ul style="list-style-type: none"> • krebserregendes Benzol ist einer der Ausgangsstoffe • verbrennt schadstoffarm 	<ul style="list-style-type: none"> • Phosgen / Chlor sind für die Herstellung notwendig • verbrennt schadstoffarm 	<ul style="list-style-type: none"> • z.Zt. umweltfreundlichstes Kartenmaterial • verbrennt schadstoffarm
Besonderheiten	negatives Image		kerbempfindlich	

Es gibt immer wieder Versuche, neben den vier üblichen Materialien für Kartenkörper PVC, ABS, PC und PET verbesserte oder neue Kunststoffe zu verwenden. Ein Beispiel dafür ist Zelluloseacetat, das zwar gute Umwelteigenschaften hat, sich aber bislang als sehr schwierig für die Massenfertigung von Karten herausstellte. Echte alternative Materialien zu Kartenkörpern aus Kunststoffen, wie etwa Papier, sind oft diskutiert, aber bisher nirgends in relevanten Stückzahlen eingesetzt worden. Die Anforderungen an Preis, Lebensdauer und Qualität an eine Karte sind nun einmal sehr hoch und momentan nur von Kunststoffen erfüllbar.

Keine echte Alternative zu den Kunststoffkartenkörpern, aber zumindest ein interessanter (oder auch kurios) zu nennender Feldversuch wurde 1996/97 in Dänemark von

¹ z.T. nach [Houdeau 97, Grün 96]

Danmønt durchgeführt.¹ Es wurden etwa 6 000 Chipkarten mit einem Kartenkörper aus schichtlaminierem und bedrucktem Birkenholz ausgegeben (8 Schichten zu je 0,1 mm). Die emittierten Karten erfüllten zwar nicht die diversen Tests nach ISO 10 373, wie etwa Biegung und Torsion, und waren logischerweise auch nicht hochprägnbar, doch etwa 90 % der Benutzer äußerten sich positiv und sagten, daß sie keine Probleme mit ihren Karten hatten. Aus Umweltsicht ist die Chipkarte aus Birkenholz leider keine Innovation, da die Holzschichten mit einem Kunststoffklebstoff zusammenlaminiert werden müssen und auch die üblichen Druckfarben notwendig sind.

3.2.2 Chipmodule




Bild 3.11 Die Evolution von Chipmodulen der Chip-on-Flex-Technik anhand einiger Beispiele, beginnend oben links mit einigen der ersten Chip-on-Flex-Module mit 8 Kontakten bis zu den heutigen Modulen mit 8 bzw. 6 Kontakten.

¹ [a la Card 97]